



## **FRONTIER PACIFIC MINING CORPORATION (TSX-V: FRP)**

Suite 875 - 555 Burrard Street  
Box 205 - Bentall Two Centre  
Vancouver, B.C. Canada, V7X 1M8  
Phone: 604-717-6488 / Fax: 604-717-6427  
[www.frontierpacific.com](http://www.frontierpacific.com) / [info@frontierpacific.com](mailto:info@frontierpacific.com)

### **Sulphide Resource Potential, Perama Hill Gold Project, Greece**

**Vancouver, British Columbia – May 26, 2008** - Frontier Pacific Mining Corporation (the “Company”) (TSX-V: FRP) today confirmed that it has received a resource potential report from Scott Wilson Mining Roscoe Postle Associates Inc. (“Scott Wilson Mining RPA”) evaluating the potential sulphide resources at Thracean Gold Mines’ (TGM) Perama Hill gold project in Greece. TGM is a wholly-owned subsidiary of Frontier Pacific. Scott Wilson Mining RPA is one of the consulting firms engaged by the Company to assist in the preparation of a bankable feasibility study in respect of the Perama Hill project. The bankable feasibility study is expected to be completed in July 2008, but in light of the recent unsolicited take-over bid for the Company by Eldorado Gold Corporation, the Company expedited Scott Wilson Mining RPA’s review of the sulphide resource potential for the project.

In the resource potential report Scott Wilson Mining RPA evaluated the potential sulphide resource utilizing the drill core assays that intercepted the sulphide mineralization discovered during the original exploration drilling on the Perama Hill project by La Source (BRGM) in 1998. The Scott Wilson Mining RPA report describes the data, assumptions and methodology used to complete the evaluation.

The sulphide potential can be separated into 2 main zones:-

- 1) Open Pit sulphide resource (known as Zone 5); and,
- 2) Underground “Feeder Zone” (known as Zone 6).

Some of the best intercepts calculated from the evaluation of Zone 5 includes:-

- 15m @ 28.1g/t Au (hole PR76 from 70m to 85m)
- 45m @ 9.2g/t Au (hole PD43 from 69m to 114m)
- 15m @ 17.3g/t Au (hole PR56 from 55m to 70m)
- 28m @ 8.1g/t Au (hole PR23 from 69m to 97m)

The open pit sulphide resource was estimated based on a gold price of US\$625/oz and US\$875/oz Whittle shells and a 2 g/t cut-off grade. Scott Wilson Mining RPA concludes that the open pit sulphide resource potential is excellent and ranges from approximately 1.5 million tonnes averaging approximately 6 grams per tonne gold to 2.5 million tonnes averaging approximately 5 grams per tonne gold.

These sulphide resource potential estimates include a gently dipping enriched zone of continuous high grade sulphide gold mineralization that is situated immediately below

the oxide gold mineralization. This high grade sulphide gold mineralization has potential for almost 1 million tonnes averaging approximately 8 grams per tonne gold and there is already sufficient drilling in parts of it to support a resource estimate.

There is not enough drilling data available to properly model the geometry and grade of the underlying feeder zone. The current preliminary model indicates that these feeders are generally too low grade and that there is not enough tonnage to support an underground bulk mining operation.

Scott Wilson Mining RPA estimates that the high grade feeder sulphide potential could be in the order of 50,000 tonnes to 300,000 tonnes averaging 10 g/t Au to 20 g/t Au. This tonnage range is based on assuming the high grade mineralization occurs either as a continuous, planar body that has a 1.5 m average thickness, 500 m strike length, and 150 m vertical extent, or as several less-continuous pipe-like bodies. Scott Wilson Mining RPA notes that most of the feeder drill hole intersections are vertical and a small number are steeply inclined.

Scott Wilson Mining RPA concludes that the open pit sulphide resource potential is excellent, the underground bulk mining sulphide resource potential is poor, and that the underground narrow vein sulphide resource potential is moderate. The underground resource potential could change when more drilling data become available.

Scott Wilson Mining RPA's resource potential report was prepared in accordance with section 2.3(2) of NI 43-101 by Mr. Luke Evans, a Qualified Person, and Mr. Tudor Ciuculescu. The complete resource potential report by Scott Wilson RPA has been lodged on SEDAR and has been posted on the Company's website ([www.frontierpacific.com](http://www.frontierpacific.com))

#### **Drill intersections from the Perama Hill "Sulphide" Potential – Zone 5 and Zone 6**

(Table format modified from ScottWilsonRPA Memorandum,  
Titled: "Perama Hill Sulphide Mineralization Resource Potential", May 2008)

Count	Hole	From (m)	To (m)	Length (m)	Au g/t	Ag g/t	Easting (m)	Northing (m)	Elevation (m)
<b>ZONE 5</b>									
1	PD04	96.8	100.0	3.2	11.9	29.5	14,035.9	17,294.5	154.1
2	PD10	77.0	91.2	14.2	9.5	13.1	14,086.3	17,485.3	156.5
3	PD12	48.0	62.0	14.0	5.5	49.5	14,142.6	17,531.4	183.5
4	PD13	47.0	49.0	2.0	6.4	43.6	14,070.7	17,589.2	172.5
5	PD15	72.6	89.0	16.4	6.9	4.0	13,979.2	17,400.7	152.8
6	PD30	48.5	55.0	6.5	4.1		14,131.3	17,486.2	187.6
7	PD39	66.8	75.0	8.2	9.5		14,103.9	17,578.3	162.3
8	PD43	69.0	114.0	45.0	9.2		14,079.2	17,337.7	151.3
9	PD48	62.9	75.0	12.1	8.5	1.4	14,078.3	17,542.2	160.7
10	PD58	88.7	101.0	12.3	7.5		14,080.0	17,441.4	150.1
11	PD64	87.8	101.0	13.2	4.0	0.3	14,030.8	17,338.9	146.7
12	PD66	90.8	101.0	10.2	7.5		14,039.2	17,314.4	143.7
13	PR100	80.0	81.0	1.0	4.9		14,014.1	17,318.7	155.4
14	PR101	78.0	90.0	12.0	6.6		14,070.7	17,315.8	158.2
15	PR19	77.0	92.0	15.0	10.0		14,084.8	17,485.3	156.1
16	PR20	72.6	89.0	16.3	6.6		13,979.0	17,400.7	152.8
17	PR23	69.0	97.0	28.0	8.1		14,078.2	17,339.0	159.9
18	PR55	46.0	60.0	14.0	6.5		14,125.1	17,554.8	181.9
19	PR56	55.0	70.0	15.0	17.3		14,103.3	17,540.3	171.2

20	PR57	44.0	44.0	0.0	6.4		14,150.1	17,554.3	193.3	
21	PR60	55.0	60.0	5.0	1.3		14,151.9	17,611.6	171.1	
22	PR62	37.0	48.0	11.0	3.8		14,158.3	17,636.9	182.5	
23	PR66	31.0	41.0	10.0	6.0		14,153.4	17,660.6	184.7	
24	PR73	61.0	80.0	19.0	11.6		14,104.4	17,465.1	172.0	
25	PR74	60.0	67.0	7.0	4.7		14,105.1	17,439.8	180.0	
26	PR75	67.0	80.0	13.0	8.1		14,089.7	17,385.7	171.4	
27	PR76	70.0	85.0	15.0	28.1		14,080.0	17,365.0	167.8	
28	PR85	88.0	110.0	22.0	6.5		14,054.1	17,490.4	136.7	
29	PR88	102.0	110.0	8.0	6.9		14,055.0	17,466.0	134.8	
30	PR89	88.0	95.7	7.7	3.1		14,083.0	17,466.2	150.5	
31	PR94	84.0	88.0	4.0	7.8		14,077.6	17,415.6	161.9	
32	PR98	89.0	100.0	11.0	14.7		14,030.6	17,366.5	148.3	
33	PR99	85.8	109.0	23.2	5.3		14,055.7	17,364.4	149.1	
34	R137	53.0	65.0	12.0	5.1	15.8	14,115.7	17,511.1	180.2	
<b>Zone 5 Averages</b>				<b>12.6</b>	<b>8.5</b>					

Count	Hole	From (m)	To (m)	Length (m)	Au g/t	Ag g/t	Easting (m)	Northing (m)	Elevation (m)
<b>ZONE 6</b>									
1	PD01	103.9	106.5	2.6	0.0		14,046.0	17,415.6	139.7
2	PD04	100.0	109.1	9.1	1.6	13.5	14,032.8	17,294.7	148.7
3	PD06	94.0	133.3	39.3	3.1	7.5	14,122.1	17,578.8	138.9
4	PD10	91.2	145.0	53.8	1.7	23.4	14,086.3	17,485.3	122.5
5	PD10	229.0	262.0	33.0	1.2	5.0	14,086.3	17,485.3	-4.9
6	PD12	62.0	141.0	79.0	2.0	6.3	14,142.6	17,531.4	137.0
7	PD13	49.0	93.0	44.0	2.2	16.1	14,070.7	17,589.2	149.5
8	PD13	111.0	182.0	71.0	1.0	5.1	14,070.7	17,589.2	74.0
9	PD15	89.0	114.3	25.3	1.0	4.1	13,979.2	17,400.7	132.0
10	PD19	44.0	48.0	4.0	2.3	14.4	14,178.9	17,703.0	171.1
11	PD19	72.0	157.2	85.2	1.2	2.6	14,178.9	17,703.0	102.5
12	PD30	55.0	56.4	1.4	3.1		14,131.3	17,486.2	183.7
13	PD31	12.8	44.0	31.2	2.5	0.8	14,045.9	17,187.0	188.2
14	PD34	25.3	58.0	32.7	1.1		14,028.5	17,221.4	179.9
15	PD34	78.0	105.0	27.0	0.9		14,028.5	17,221.4	130.1
16	PD35	31.1	98.0	66.9	1.4		14,190.0	17,630.5	164.0
17	PD39	75.0	128.4	53.4	2.4		14,096.0	17,577.9	132.6
18	PD43	68.1	69.0	0.9	1.7		14,079.5	17,337.7	174.3
19	PD43	114.0	131.1	17.1	2.8		14,078.8	17,337.8	120.3
20	PD45	109.0	214.0	105.0	3.1	0.1	13,989.7	17,441.5	73.9
21	PD47	122.8	155.0	32.2	1.3		14,031.6	17,437.6	103.3
22	PD48	75.0	143.0	68.0	0.8		14,078.3	17,542.2	120.6
23	PD49	91.8	147.4	55.6	0.8		14,032.7	17,491.6	113.9
24	PD50	68.8	143.9	75.1	1.6		14,128.8	17,634.9	114.0
25	PD55	25.9	72.0	46.1	1.7		14,225.4	17,691.9	173.5
26	PD58	101.0	162.2	61.2	1.8		14,079.1	17,441.5	113.4
27	PD64	101.0	102.0	1.0	1.4		14,030.8	17,338.9	139.6
28	PD64	142.0	160.0	18.0	8.8		14,030.8	17,338.9	90.1
29	PD66	101.0	115.0	14.0	1.9		14,039.2	17,314.4	131.6
30	PD66	143.0	171.0	28.0	5.1		14,039.2	17,314.4	82.6
31	PD68	74.6	154.0	79.4	2.4		14,052.3	17,272.0	127.6
32	PD71	64.6	118.0	53.4	1.7		14,179.9	17,584.9	145.6
33	PD72	42.0	54.5	12.5	0.1		14,091.3	17,635.9	169.0
34	PD72	132.0	143.0	11.0	1.6		14,091.3	17,635.9	79.7
35	PD73	59.5	98.0	38.5	2.8		14,084.8	17,293.5	160.6
36	PD74	82.3	104.0	21.7	1.2		14,062.9	17,387.4	153.5
37	PD74	135.0	200.0	65.0	1.9		14,062.9	17,387.4	79.2
38	PD75	96.5	134.9	38.4	2.2		14,084.8	17,409.4	138.9
39	PR100	81.0	87.0	6.0	1.7		14,014.1	17,318.7	151.9
40	PR18	20.0	34.0	14.0	3.1	20.9	14,246.2	17,690.9	198.0

41	PR19	92.0	105.0	13.0	2.7		14,084.8	17,485.3	142.1
42	PR20	89.0	105.0	16.0	1.3		13,979.0	17,400.7	136.7
43	PR22	31.3	87.0	55.7	2.2		14,192.4	17,631.0	169.5
44	PR24	43.6	48.8	5.2	1.5		14,180.1	17,704.6	170.9
45	PR24	69.6	105.0	35.4	1.4		14,180.1	17,704.6	129.8
46	PR27	18.0	51.0	33.0	3.4		14,022.3	17,193.3	181.0
47	PR53	119.0	120.0	1.0	0.3		14,030.0	17,415.0	124.4
48	PR55	36.6	46.0	9.4	0.2		14,125.1	17,554.8	193.6
49	PR57	44.0	63.0	19.0	4.2		14,150.1	17,554.3	183.8
50	PR59	35.0	60.0	25.0	0.5		14,184.7	17,608.8	185.4
51	PR60	60.0	70.0	10.0	2.9		14,151.9	17,611.6	163.6
52	PR61	53.0	70.0	17.0	1.1		14,131.8	17,612.8	163.4
53	PR62	31.6	37.0	5.4	0.4		14,158.3	17,636.9	190.7
54	PR62	48.0	62.7	14.7	1.3		14,158.3	17,636.9	169.6
55	PR63	56.0	70.0	14.0	3.0		14,101.7	17,615.5	158.4
56	PR64	54.0	70.0	16.0	0.5		14,109.8	17,634.9	156.8
57	PR66	41.0	60.0	19.0	1.6		14,153.4	17,660.6	170.2
58	PR68	40.0	46.7	6.7	0.1		14,047.3	17,576.4	175.6
59	PR70	66.0	70.0	4.0	0.6		14,054.9	17,540.5	158.6
60	PR72	46.0	48.9	2.9	4.4		14,130.3	17,466.9	192.7
61	PR74	67.0	68.0	1.0	2.0		14,105.1	17,439.8	176.0
62	PR75	63.7	67.0	3.3	2.8		14,089.7	17,385.7	179.5
63	PR75	80.0	81.0	1.0	2.9		14,089.7	17,385.7	164.4
64	PR76	85.0	86.0	1.0	2.8		14,080.0	17,365.0	159.8
65	PR79	60.0	89.0	29.0	0.5		14,064.2	17,244.5	162.8
66	PR80	25.0	42.0	17.0	1.7		14,004.5	17,216.2	183.7
67	PR81	16.5	22.0	5.5	0.4	0.3	13,989.4	17,189.4	190.5
68	PR81	34.0	44.0	10.0	2.2		13,999.3	17,189.4	173.4
69	PR83	60.0	71.8	11.8	0.6		13,977.9	17,366.2	164.6
70	PR86	113.0	120.0	7.0	0.4		14,009.2	17,464.0	120.2
71	PR87	124.0	131.0	7.0	6.5		14,030.1	17,460.6	110.9
72	PR89	95.7	120.0	24.3	2.9		14,083.0	17,466.2	134.5
73	PR90	117.7	121.0	3.3	8.1		14,004.8	17,439.9	117.7
74	PR94	88	96	8	2.1		14,077.6	17,415.6	155.9
75	PR95	100	102.1	2.1	2.3		14,030.6	17,388.9	143.0
76	PR97	82.3	99.9	17.7	1.5		14,005.4	17,365.2	146.1
77	PR98	100	107.7	7.7	0.7		14,030.6	17366.5	138.9
78	PR99	109	111	2.0	2.3		14,055.7	17,364.4	136.4
79	R129	29	30	1.0	2.5		14,244.6	17,660.4	195.3
<b>Zone 6 Averages</b>				<b>25.4</b>	<b>1.9</b>				

Preliminary metallurgical tests on samples of the low sulphide mineralization were performed by BRGM in 1998 and again by Newmont Mining in 2002 showing that gold extractions between 87% and 95% were possible on this mineralization. This data was contained within the information package owned by Thracean Gold Mining when the company was purchased by Frontier Pacific Mining Corporation in 2004.

The Bankable Feasibility Study by Aker Solutions that is expected to be completed in July 2008 will contemplate only the development of an open pit gold mine extracting the oxide resource during a 9 year mine life.

---

On Behalf of the Board of Directors,

**FRONTIER PACIFIC MINING CORPORATION**

***“Peter F. Tegart”***

Peter F. Tegart, P. Geo.,  
President & CEO

*The TSX Venture Exchange (the "Exchange") has not reviewed and does not accept responsibility for the accuracy or adequacy of this news release. The Exchange has in no way passed upon the merits of the proposed transaction and has neither approved nor disapproved the contents of this news release.*

*This news release may contain forward-looking statements that are based on Frontier Pacific expectations, estimates and projections regarding its business and the economic environment in which it operates. In particular, estimates of the sulphide resource potential are based on drill results compiled by parties other than the Company some years ago and not on systematic drilling or assay results undertaken by the Company. These statements are not guarantees of future performance and involve risks and uncertainties that are difficult to control or predict. Therefore, actual outcomes and results may differ materially from those expressed in these forward-looking statements and readers should not place undue reliance on such statements. Statements speak only as of the date on which they are made, and the Company undertakes no obligation to update them publicly to reflect new information or the occurrence of future events or circumstances, unless otherwise required to do so by law.*